

COAXIAL CONNECTOR, 1.0/2.3 C50, 50 Ohm, Right angle cable plug (male)

16_1023-C50-2-3/111_N

Properties

- Suitable for the insertion of layout connectors DIN 41612
- Fast and easy assembly
- Applicable in frequencies up to 4 GHz



Product configuration		
Interface type	Gender	Standard
1.0/2.3 C50	plug	DIN 41626/2

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

Electrical data	
Impedance	50 Ω
Interface frequency	4 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 1 GHz	33 dB	1.05
1 GHz ... 2 GHz	27 dB	1.09
2 GHz ... 4 GHz	25 dB	1.12

Mechanical data	
Weight	0.0037 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	crimped

COAXIAL CONNECTOR, 1.0/2.3 C50, 50 Ohm, Right angle cable plug (male)

16_1023-C50-2-3/111_N

Environmental data		
Operation temperature	-55 °C ... 125°C	
Ordering Information Table		
Item number	Item description	Packaging type
22650726	16_1023-C50-2-3/111_NE	Single
Suitable cables		
Cable group	U4 - 2 mm / 50 Ohm	
Suitable cables	K_02252_D	
	G_02232_D	
	ENVIROFLEX_316_D	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3184 / Date of publication: 25.11.2023 / uncontrolled copy