

**COAXIAL CONNECTOR, H4, 50 Ohm, Straight cable plug (male)**

11\_H4-50-3-1/133\_N

**Properties**

- Working voltage up to 1.6 kV rms in mated condition
- Applicable in frequencies up to 300 MHz



Product configuration	
Interface type	Gender
H4	plug

  

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

  

Electrical data	
Impedance	50 Ω
Interface frequency	0.3 GHz

  

Mechanical data	
Weight	0.0228 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	clamped

  

Environmental data	
Operation temperature	-65 °C ... 165°C

**COAXIAL CONNECTOR, H4, 50 Ohm, Straight cable plug (male)**

11\_H4-50-3-1/133\_N

Ordering Information Table		
Item number	Item description	Packaging type
22541732	11_H4-50-3-1/133_NE	Single

Suitable cables	
Cable group	X25 - 3 mm / 50 Ohm
	U9 - 3 mm / 50 Ohm
	U7 - 3 mm / 50 Ohm
	U11 - 3 mm / 50 Ohm
Suitable cables	RG_58_C/U
	G_03232
	GX_03272

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3640 / Date of publication: 25.11.2023 / uncontrolled copy