

COAXIAL CONNECTOR, MFBX, 50 Ohm, Straight PCB jack (female)

82_MFBX-50-0-3/111_N

Properties

- High axial float
- Price/Performance optimized
- Blind mateable
- Reliable and secure connection



Product configuration		
Interface type	Gender	Standard
MFBX	jack	HUBER+SUHNER MFBX
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPRO Plating
Insulator	LCP (Liquid crystal polymer)	
Electrical data		
Impedance	50 Ω	
Interface frequency	6 GHz	
Mechanical data		
Weight	0.000602 kg	
Mating cycles	50	
Board mounting type	through holes	
Height above PCB HA	3.3 mm	
Height of stand off HS	0.5 mm	
Environmental data		
Operation temperature	-55 °C ... 155°C	
Ordering Information Table		
Item number	Item description	Packaging type
85025488	82_MFBX-50-0-3/111_NE	Single

COAXIAL CONNECTOR, MFBX, 50 Ohm, Straight PCB jack (female)

82_MFBX-50-0-3/111_N

Additional Information

Remarks	PCB connector with stand-offs
---------	-------------------------------

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1335 / Date of publication: 26.11.2023 / uncontrolled copy