Data Sheet



Coaxial Cable Connector 11_BNT-50-4-1/103_N

Description

Straight cable plug

Interface standards SUHNER-BNT



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \, \Omega \\ \text{Interface frequency max.} & 3 \, \text{GHz} \end{array}$

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0218 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -50 °C to 125 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing DOU-00007883
Catalogue drawing DOU-00007643
Assembly instruction DOC-0000179264

Ordering Information

Single package 11_BNT-50-4-1/103_NE

Additional Information

Remarks

Triaxial Connector

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.