Data Sheet



Coaxial PCB Connector 81_MCX-50-0-6/111_N

Description

Straight PCB plug

Interface Standards IEC 60169-36_CECC 22220



Technical Data

Electrical Data

Impedance 50Ω Interface frequency max. 6 GHz

Mechanical Data

Board mounting type through holes Weight 0.0009 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -55 °C to 155 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00013049
Catalogue drawing DCA-00013051

Ordering Information

 Bulk 100 pcs package
 81_MCX-50-0-6/111_NH

 Single package
 81_MCX-50-0-6/111_NE

Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.