





NOTES:
1.MATERIAL:
HOUSING: LCP ZENITE 6130L 30% G/F UL94 V-0
COLOR: BLACK
CONTACT: BRASS C5191H T=0.15mm

2.FINISH:
CONTACT: GOLD FLASH/TIN PLATING ON CONTACT AREA
100u" MIN.TIN PLATING ON SOLDERTAILS
50u" MIN.NICKEL UNDERPLATING OVER ALL
BOARD LOCK: 100u" MIN.TIN PLATION ON SOLDERTAILS
50u" MIN.TIN NICKEL UNDERPLATING OVER ALL

SD CARD PIN DESIGN			
PIN#	Name	Type	Description
1	CD/DAT3	I/O/PP	Card Detect/Data Line (BK3)
2	CMD	PP	Command/Response
3	Vss1	S	Supply voltage ground
4	VDD	S	Supply voltage
5	CLK	I	Clock
6	Vss2	S	Supply voltage ground
7	DAT0	I/O/PP	Data line (BK0)
8	DAT1	I/O/PP	Data line (BK1)
9	DAT2	I/O/PP	Data line (BK2)



P.C.B LAYOUT
TOLERANCE±0.05

SCALE		UNLESS OTHERWISE SPECIFIED TOLERANCE	
DRAWN 陈志杰		ANG 0 ±0.3 ±0.2 ±0.05	
CHECKED		UNIT: mm	
APPROVED		DRAWN NAME	
SIZE: A4		PRODUCT NO.	
REV: A		FILE NAME: SD卡座	

SD 卡座 - PUSH TYPE