



Technical Characteistics:

1. Working temperature: -60°C to $+200^{\circ}\text{C}$
2. Working current: $\varnothing 1.5 - 10\text{A}$
3. Working voltage: 400V (AC)
4. Contact resistance: $\leq 2.5\text{m}\Omega$
5. Insulation resistance: Normal: $\geq 1000\text{M}\Omega$
High humidity: $\geq 20\text{M}\Omega$
6. Shell mateial: Aluminum alloy
7. Insulation material: Bakelite
8. Surface treatment: Anodizing, 96 hours of salt spray tes

| | | | | | | | |
|-------------------|-----|---------------------|--------|------------|----|--------|-----------------------|
| GENERAL TOLERANCE | | ANGLE TOLERANCE | | PROJECTION | | TITLE | PRODUCT SPECIFICATION |
| x. ± 0.60 | | x. $\pm 5^{\circ}$ | | UNITS | mm | | |
| .x ± 0.38 | | .x $\pm 3^{\circ}$ | | SHEET SIZE | A4 | SERIES | 2PM18K4QB2 |
| .xx ± 0.25 | | .xx $\pm 2^{\circ}$ | | | | | |
| SCALE | 2:1 | SHEET | 1 OF 1 | | | | |
| DRAWING NO | | | | | | | |