



**Technical Characteistics:**

1. Working temperature:  $-60^{\circ}\text{C}$  to  $+200^{\circ}\text{C}$
2. Working current:  $\varnothing 1.0 - 5\text{A}$
3. Working voltage:  $400\text{V (AC)}$
4. Contact resistance:  $\leq 5\text{m}\Omega$
5. Insulation resistance: Normal:  $\geq 1000\text{M}\Omega$   
High humidity:  $\geq 20\text{M}\Omega$
6. Shell mateial: Aluminum alloy
7. Insulation material: Bakelite
8. Surface treatment: Anodizing, 96 hours of salt spray tes

|                   |               |                     |                    |            |    |        |                       |
|-------------------|---------------|---------------------|--------------------|------------|----|--------|-----------------------|
| GENERAL TOLERANCE |               | ANGLE TOLERANCE     |                    | PROJECTION |    | TITLE  | PRODUCT SPECIFICATION |
| x. $\pm 0.60$     | .x $\pm 0.38$ | .x $\pm 5^{\circ}$  | .x $\pm 3^{\circ}$ | UNITS      | mm | SERIES |                       |
| .xx $\pm 0.25$    |               | .xx $\pm 2^{\circ}$ |                    | SHEET SIZE | A4 |        | 2PM22K10QB2           |
| SCALE             | 2:1           | SHEET               | 1 OF 1             |            |    |        |                       |
| DRAWING NO        |               |                     |                    |            |    |        |                       |