

COAXIAL CONNECTOR, NEX10, 50 Ohm, Straight bulkhead cable jack (female)

24_NEX10-50-2-1/033_-

Properties

- PIM Stable Interface
- Compact and space saving
- Operating frequency up to 20 GHz
- Excellent return loss and electrical performance
- Interface safe from installation errors



Product configuration		
Interface type	Gender	Standard
NEX10	jack	NEX10

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Silver Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

Electrical data	
Impedance	50 Ω
Interface frequency	20 GHz

Mechanical data	
Cable entry centre contact	soldered
Cable entry outer contact	soldered

Environmental data	
Operation temperature	-55 °C ... 125°C

Ordering Information Table		
Item number	Item description	Packaging type
85095339	24_NEX10-50-2-1/033_-Y	Bulk 100 pcs

COAXIAL CONNECTOR, NEX10, 50 Ohm, Straight bulkhead cable jack (female)

24_NEX10-50-2-1/033_-

Suitable cables	
Cable group	Y16 - 2 mm / 50 Ohm
Suitable cables	SUCOFORM_86

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2603 / Date of publication: 25.11.2023 / uncontrolled copy