

COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead receptacle, jack (female)

22_QMA-50-0-34/133_N

Properties

- Excellent electrical performance
- High packing density
- Applicable in frequencies up to 18 GHz
- Easy to mate - No torque or tooling required
- Return loss optimized DC to 6 GHz



Product configuration

Interface type	Gender	Standard
QMA	jack	QMA QLF compliant

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Electrical data

Impedance	50 Ω
Interface frequency	18 GHz

Mechanical data

Flange type	hexagonal flange / hex 11
Tab style	Standard

Environmental data

Operation temperature	-40 °C ... 85°C
-----------------------	-----------------

Ordering Information Table

Item number	Item description	Packaging type
84061333	22_QMA-50-0-34/133_NH	Bulk 100 pcs

COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_QMA-50-0-34/133_N

Additional Information

Remarks	With panel seal
---------	-----------------

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2791 / Date of publication: 26.11.2023 / uncontrolled copy