

COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead receptacle, jack (female)

22_QMA-50-0-7/133_N

Properties

- Excellent electrical performance
- High packing density
- Applicable in frequencies up to 18 GHz
- Easy to mate - No torque or tooling required
- Return loss optimized DC to 6 GHz



Product configuration

Interface type	Gender	Standard
QMA	jack	QMA QLF compliant

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Mechanical data

Weight	0.0021 kg
Mating cycles	100
Flange type	round flange / dia. 7.6
Tab style	Standard

Environmental data

Operation temperature	-40 °C ... 85°C
-----------------------	-----------------

Ordering Information Table

Item number	Item description	Packaging type
84001926	22_QMA-50-0-7/133_NF	Bulk 50 pcs

COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_QMA-50-0-7/133_N

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2788 / Date of publication: 26.11.2023 / uncontrolled copy