

## Coaxial Cable Connector 24\_N-50-7-8/133\_N

### Description

Straight bulkhead cable feed through

#### Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	clamped
Weight	0.0525 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

### Related Documents

Catalogue drawing	DCA-00009272
Assembly instruction	DOC-0000179854

### Ordering Information

Single package	24_N-50-7-8/133_NE
----------------	--------------------

### Additional Information

Suitable cables	RG_213 _/U, GX_07272, RG_214 _/U
-----------------	----------------------------------