

## Coaxial Cable Connector 16\_MMBX-50-2-2/111\_N

### Description

Right angle cable plug

Interface standards  
SUHNER-MMBX



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 12.4 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact crimped  
Weight 0.0011 kg

#### Environmental Data

Operating temperature -55 °C to 155 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

### Related Documents

Outline drawing DOU-00006252  
Catalogue drawing DOU-00006254  
Assembly instruction DOC-0000178673

### Ordering Information

Single package 16\_MMBX-50-2-2/111\_NE  
Bulk 100 pcs package 16\_MMBX-50-2-2/111\_NH

### Additional Information

Suitable cables ENVIROFLEX\_316\_D, K\_02252\_D, G\_02232\_D