

Coaxial Cable Connector

11_716-50-5-4/003_-

Description

Straight cable plug

Interface standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
Frequency range	DC to 2.5 GHz
Return loss	32 dB

Mechanical Data

Centre contact	soldered
Outer contact	clamped
Weight	0.1491 kg

Environmental Data

Operating temperature	-40 °C to 85 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	NR (Natural Rubber)	

Related Documents

Outline drawing	DOU-00007026
Catalogue drawing	DOU-00007028
Assembly instruction	DOC-0000180978

Ordering Information

Bulk 10 pcs package	11_716-50-5-4/003_-Z
---------------------	----------------------

Additional Information

Suitable cables	SUCOFEED_1/4_HF, SUCOFEED_1/4_HF_FR, FSJ1-50
-----------------	--