

## Coaxial Cable Connector 11\_N-50-3-51/133\_N

### Description

Straight cable plug

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact soldered  
Weight 0.0435 kg

#### Environmental Data

Operating temperature -55 °C to 70 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Catalogue drawing DOU-00007863  
Assembly instruction DOC-0000180866

### Ordering Information

Single package 11\_N-50-3-51/133\_NE

### Additional Information

Suitable cables SUCOFORM\_141, EZ\_141\_TP\_M17, MULTIFLEX\_141