


# COAXIAL CONNECTOR, N, 50 Ohm, Straight panel cable jack (female), flange mount

25\_N-50-2-14/133\_N

## Properties

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration		
Gender	Standard	
jack	IEC 61169-16_MIL-STD-348A/304_CECC 22210	
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Electrical data		
Impedance	50 Ω	
Interface frequency	18 GHz	
Mechanical data		
Weight	0.0427 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	soldered	
Environmental data		
Operation temperature	-65 °C ... 165°C	
Ordering Information Table		
Item number	Item description	Packaging type
22641303	25_N-50-2-14/133_NE	Single

## COAXIAL CONNECTOR, N, 50 Ohm, Straight panel cable jack (female), flange mount 25\_N-50-2-14/133\_N

Suitable cables	
Cable group	Y3 - 2 mm / 50 Ohm Y16 - 2 mm / 50 Ohm
Suitable cables	SR_86_TP_M17 SUCOFORM_86
Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2493 / Date of publication: 25.11.2023 / uncontrolled copy