

COAXIAL CONNECTOR, QN, 50 Ohm, Straight bulkhead cable jack (female)

24_QN-50-3-2/133_N

Properties

- Same performance but smaller than N-Interface
- High packing density
- Applicable in frequencies up to 11 GHz
- Easy to mate - No torque or tooling required



Product configuration		
Interface type	Gender	Standard
QN	jack	QN QLF compliant

Interface and material data		
Piece parts	Material	Plating
Centre contact	Bronze	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data	
Impedance	50 Ω
Interface frequency	11 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2 GHz	32 dB	1.05
2 GHz ... 2.5 GHz	30 dB	1.65

Mechanical data	
Weight	0.02 kg
Mating cycles	100
Cable entry centre contact	crimped

COAXIAL CONNECTOR, QN, 50 Ohm, Straight bulkhead cable jack (female)

24_QN-50-3-2/133_N

Mechanical data		
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-40 °C ... 125°C	
Ordering Information Table		
Item number	Item description	Packaging type
23033402	24_QN-50-3-2/133_NE	Single
Suitable cables		
Cable group	U7 - 3 mm / 50 Ohm	
Suitable cables	RG_58_C/U	
	G_03232	
	GX_03272-04	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2589 / Date of publication: 25.11.2023 / uncontrolled copy