


COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead cable jack (female)

24_QMA-50-2-1/111_N

Properties

- Excellent electrical performance
- High packing density
- Applicable in frequencies up to 18 GHz
- Easy to mate - No torque or tooling required
- Return loss optimized DC to 6 GHz



Product configuration		
Interface type	Gender	Standard
QMA	jack	QMA QLF compliant

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPRO Plating
Washer	Bronze	SUCOPRO Plating

Electrical data	
Impedance	50 Ω
Interface frequency	18 GHz

Mechanical data	
Weight	0.0041 kg
Mating cycles	100
Cable entry centre contact	plugged
Cable entry outer contact	soldered

Environmental data	
Operation temperature	-40 °C ... 85°C

COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead cable jack (female)

24_QMA-50-2-1/111_N

Ordering Information Table		
Item number	Item description	Packaging type
23017742	24_QMA-50-2-1/111_NE	Single
23017743	24_QMA-50-2-1/111_NH	Bulk 100 pcs

Suitable cables	
Cable group	Y3 - 2 mm / 50 Ohm
	Y16 - 2 mm / 50 Ohm
	Y11 - 2 mm / 50 Ohm
Suitable cables	SUCOFORM_86
	SR_86_TP_M17
	MULTIFLEX_86

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2599 / Date of publication: 25.11.2023 / uncontrolled copy