

**COAXIAL CONNECTOR, N, 50 Ohm, Right angle cable plug (male)**

16\_N-50-10-1/103\_U

**Properties**

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration		
Interface type	Gender	Standard
N	plug	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer conductor	Brass	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data	
Impedance	50 Ω
Interface frequency	11 GHz

Mechanical data	
Weight	0.0557 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	crimped

Environmental data	
Operation temperature	-65 °C ... 165°C

**COAXIAL CONNECTOR, N, 50 Ohm, Right angle cable plug (male)**

16\_N-50-10-1/103\_U

Ordering Information Table		
Item number	Item description	Packaging type
23002552	16_N-50-10-1/103_UV	Bulk 20 pcs
Suitable cables		
Cable group	S39 - 10 mm / 50 Ohm	
Suitable cables	S_10172_B-11	
	S_10162_B-11	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3105 / Date of publication: 25.11.2023 / uncontrolled copy