

COAXIAL CONNECTOR, BNO, X Ohm, Straight cable plug (male)

11_BNO-0-4-1/133_N

Properties

- Used with balanced twin-conductor cables with 75 ohm to 130 ohm impedance
- Suitable for applications up to 200 MHz
- Ideal for computer networks and process control



Product configuration		
Interface type	Gender	Standard
BNO	plug	IEC 60169-22
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	ETFE (Ethylene tetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating
Electrical data		
Interface frequency	0.2 GHz	
Mechanical data		
Weight	0.0177 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-50 °C ... 125°C	

COAXIAL CONNECTOR, BNO, X Ohm, Straight cable plug (male)

11_BNO-0-4-1/133_N

Ordering Information Table		
Item number	Item description	Packaging type
22541080	11_BNO-0-4-1/133_NE	Single
22649903	11_BNO-0-4-1/133_NH	Bulk 100 pcs

Suitable cables	
Cable group	V1 - 2 mm / 78 Ohm
Suitable cables	RG_108_A/U

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3652 / Date of publication: 25.11.2023 / uncontrolled copy