


# COAXIAL CONNECTOR, MMCX, 50 Ohm, Right angle PCB jack (female)

85\_MMCX-50-0-1/111\_O

## Properties

- Very small size
- Easy to connect and disconnect
- Wide range of board connectors and cable connectors available



Product configuration		
Interface type	Gender	Standard
MMCX	jack	HUBER+SUHNER-MMCX
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Electrical data		
Impedance	50 Ω	
Interface frequency	6 GHz	
Mechanical data		
Weight	0.0006 kg	
Mating cycles	500	
Board mounting type	through holes	
Number of printlegs	4	
Height above PCB HA	3.8 mm	
Height of stand off HS	0 mm	
Disengagement force (to)	15 N	
Engagement force max	15 N	
Environmental data		
Operation temperature	-55 °C ... 155°C	

**COAXIAL CONNECTOR, MMCX, 50 Ohm, Right angle PCB jack (female)**

85\_MMCX-50-0-1/111\_O

Ordering Information Table		
Item number	Item description	Packaging type
22645968	85_MMCX-50-0-1/111_OE	Single
22646636	85_MMCX-50-0-1/111_OH	Bulk 100 pcs

Additional Information	
Remarks	PCB connector without stand-offs

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P1282 / Date of publication: 26.11.2023 / uncontrolled copy