

# COAXIAL CONNECTOR, SMA, 50 Ohm, Straight panel receptacle, jack (female), flange mount

23\_SMA-50-0-13/111\_N

## Properties

- Excellent corrosion resistance in a wide range of environments
- High salt mist resistant
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
SMA	jack	IEC 60169-15_MIL-STD-348A/310_CECC 22110
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Electrical data		
Impedance	50 Ω	
Interface frequency	18 GHz	
Mechanical data		
Weight	0.0023 kg	
Mating cycles	500	
Flange type	2-hole flange / 16 X 5.7	
Tab style	Standard	
Environmental data		
Operation temperature	-65 °C ... 125 °C	

**COAXIAL CONNECTOR, SMA, 50 Ohm, Straight panel receptacle, jack (female), flange mount**

23\_SMA-50-0-13/111\_N

Ordering Information Table		
Item number	Item description	Packaging type
22640097	23_SMA-50-0-13/111_NE	Single
22658873	23_SMA-50-0-13/111_NH	Bulk 100 pcs

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2711 / Date of publication: 16.02.2024 / uncontrolled copy