


# COAXIAL CONNECTOR, N, 50 Ohm, Straight bulkhead receptacle, jack (female)

22\_N-50-0-23/133\_N

## Properties

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration		
Interface type	Gender	Standard
N	jack	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	11 GHz

Mechanical data	
Weight	0.0208 kg
Mating cycles	500
Flange type	round flange / dia. 15.9
Tab style	solder end

Environmental data	
Operation temperature	-65 °C ... 165°C

Ordering Information Table		
Item number	Item description	Packaging type
22651448	22_N-50-0-23/133_NF	Bulk 50 pcs

---

**COAXIAL CONNECTOR, N, 50 Ohm, Straight bulkhead receptacle, jack (female)**  
22\_N-50-0-23/133\_N

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2796 / Date of publication: 26.11.2023 / uncontrolled copy