

COAXIAL CONNECTOR, MMPX, 50 Ohm, Edge mount PCB jack (female)

92_MMPX-S50-0-1/111_N

Properties

- Excellent electrical performance at smallest dimensions
- Broadband electrical characteristics
- Mechanically very robust
- Fits a wide range of cable types



Product configuration		
Interface type	Gender	Standard
MMPX	jack	HUBER+SUHNER MMPX STD (Patent US 7,294,023)

Material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO / Gold Plating
Outer conductor	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Body	Brass	SUCOPRO / Gold Plating
Insulator	PTFE (Polytetrafluoroethylene)	

Electrical data	
Impedance	50 Ω
Operating frequency	90 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 26.5 GHz	22 dB	1.17
26.5 GHz ... 50 GHz	20 dB	1.22
50 GHz ... 67 GHz	20 dB	1.22

Mechanical data	
Weight	0.0005 kg
Mating cycles	100
Board mounting type	edge mount
Disengagement force (to)	30 N
Engagement force max	30 N

COAXIAL CONNECTOR, MMPX, 50 Ohm, Edge mount PCB jack (female)

92_MMPX-S50-0-1/111_N

Environmental data	
Operation temperature	-65 °C ... 155°C

Ordering Information Table			
Item number	Item description	Packaging type	Packaging information
84009138	92_MMPX-S50-0-1/111_NM	Bulk 10 pcs	Available in blister tape only!
84009140	92_MMPX-S50-0-1/111_NM-1	Tape and Reel	500 pcs/reel

Additional Information	
Remarks	Bandwidth expansion to 90 GHz when used in combination with adaptor 33_MMPX-PC1-50-1/111_NE or cable connector 11_MMPX-50-1-6/11-_UE (Cable: Multiflex_53-02). Decoupling tool MMPX shall be used (74_Z-0-0-491/74_Z-0-0-555)!

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1150 / Date of publication: 17.10.2023 / uncontrolled copy