

COAXIAL CONNECTOR, BNO, X Ohm, Straight panel receptacle, jack (female), flange mount

23_BNO-0-0-2/133_N

Properties

- Used with balanced twin-conductor cables with 75 ohm to 130 ohm impedance
- Suitable for applications up to 200 MHz
- Ideal for computer networks and process control



Product configuration		
Interface type	Gender	Standard
BNO	jack	IEC 60169-22
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	ETFE (Ethylene tetrafluoroethylene)	
Electrical data		
Interface frequency	0.2 GHz	
Mechanical data		
Weight	0.0102 kg	
Mating cycles	500	
Flange type	square flange / 17.5 X 17.5	
Tab style	solder end	
Environmental data		
Operation temperature	-50 °C ... 125°C	
Ordering Information Table		
Item number	Item description	Packaging type
22541085	23_BNO-0-0-2/133_NE	Single

COAXIAL CONNECTOR, BNO, X Ohm, Straight panel receptacle, jack (female), flange mount

23_BNO-0-0-2/133_N

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2744 / Date of publication: 26.11.2023 / uncontrolled copy