


COAXIAL CONNECTOR, MMBX, 50 Ohm, Straight PCB jack (female)

82_MMBX-S50-0-13/111_N

Properties

- Smallest board-to-board distance
- Very high frequencies
- Excellent return loss values
- Blind mateable
- Reliable and secure connection

**Product configuration**

Interface type	Gender	Standard
MMBX	jack	HUBER+SUHNER-MMBX

Interface and material data

Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	LCP (Liquid crystal polymer)	

Electrical data

Impedance	50 Ω
Interface frequency	12.4 GHz

Mechanical data

Weight	0.0008 kg
Mating cycles	100
Board mounting type	surface mount
Height above PCB HA	4.1 mm
Height of stand off HS	0.6 mm
Disengagement force (to)	30 N
Engagement force max	30 N

Environmental data

Operation temperature	-55 °C ... 155 °C
-----------------------	-------------------

COAXIAL CONNECTOR, MMBX, 50 Ohm, Straight PCB jack (female)

82_MMBX-S50-0-13/111_N

Ordering Information Table		
Item number	Item description	Packaging type
84032435	82_MMBX-S50-0-13/111_NE	Single
23036608	82_MMBX-S50-0-13/111_NH	Bulk 100 pcs
23041511	82_MMBX-S50-0-13/111_NM	Tape and Reel

Additional Information	
Remarks	PCB connector with stand-offs

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1327 / Date of publication: 17.04.2024 / uncontrolled copy